

(19) World Intellectual Property
Organization
International Bureau



533129

(43) International Publication Date
13 May 2004 (13.05.2004)

PCT

(10) International Publication Number
WO 2004/039194 A1

- (51) International Patent Classification⁷: A43B 3/24
// 3/28, A62B 18/08
- (21) International Application Number:
PCT/NO2003/000358
- (22) International Filing Date: 28 October 2003 (28.10.2003)
- (25) Filing Language: Norwegian
- (26) Publication Language: English
- (30) Priority Data:
20025231 31 October 2002 (31.10.2002) NO
- (71) Applicant (for all designated States except US):
FORSVARETS FORSKNING SINSTITUTT [NO/NO];
P.O. Box 25, N-2027 Kjeller (NO).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): HALSNES, Odd
[NO/NO]; Måstad, N-1866 Båstad (NO).
- (74) Agents: ONSAGERS AS et al.; P.O. Box 6963 St. Olavs
plass, N-0130 Oslo (NO).

(81) Designated States (national): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, EG, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES,

[Continued on next page]

(54) Title: EXHALATION SYSTEM



(57) Abstract: An exhalation system is provided for a helmet or face mask, which helmet or face mask covers the whole or parts of the area of the face's exhalation organs, the nose and mouth, with a chin guard. The system is characterised in that the chin guard is provided with an internal closed cavity which has an opening towards the interior of the helmet or the face mask on the inside of the chin guard and an additional opening towards the outside of the chin guard. The opening towards the interior of the helmet is relatively large and is in the form of one large opening or a small number of large openings which offer the least possible resistance and maintain the velocity of the exhalation air in the best possible manner.



FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Exhalation system

The present invention relates to an exhalation system for a helmet or face mask, which helmet or face mask covers the whole or parts of the area of the face's exhalation organs, nose and mouth.

5 People using helmets of various types or different kinds of face masks, particularly with visors or goggles, are familiar with the problems that arise when exhaled air from the person's exhalation organs such as the nose or mouth causes misting on glasses or visors together with a raised level of CO₂ in the immediate vicinity of the area where the person breathes in. This makes it difficult to see and reduces
10 visibility while at the same time a person who is physically active may experience increased levels of CO₂ as a problem leading to a reduced state of alertness, nausea, dizziness and at worst a loss of consciousness. Exhalation in a closed helmet, moreover, creates unpleasant conditions with regard to odour, etc. inside the helmet.

The problem applies to motorcycle helmets and helmets for use by soldiers, police
15 and security personnel, when the helmet covers the mouth and/or nose and particularly when the helmet has a visor or goggles. Such helmets are less able to replace air from the area round the nose/mouth.

A number of face masks are also employed which, in combination with a visor or goggles, create a space round the face which covers nose and mouth, thereby
20 creating the same situation.

A number of helmets and face masks therefore have a perforated or otherwise partly open area at the nose and mouth to permit the escape of exhaled air. The problem, however, is that such perforated areas have relatively strong resistance and whilst the problem of moist exhaled air (which causes misting) may perhaps be solved
25 since the exhaled air is mixed with and cooled by fresh air in front of the openings, there will be very little effect on problems with a raised concentration of CO₂, since the resistance is too great to permit this gas to be removed.

Nor is it desirable to have a large opening in the protection round nose and mouth offered by a helmet or face mask. This is due to several factors, such as deficient
30 protection (in the case of a motorcycle helmet, for example), unfavourable wind and weather conditions, particularly at high speed where snow and rain, etc. penetrate right into the person's breathing organ. This also results in a substantial reduction in comfort. When the air outside the helmet moves at a velocity against the helmet that is greater than the velocity of the air exhaled from nose or mouth, moreover,
35 exhaled air will not be removed to a noticeable extent, but only attenuated in the nose or mouth region.

A number of solutions may also be envisaged where excess pressure is created in the helmet in order to assist in removing used air while simultaneously drawing in fresh air. Such systems, however, are expensive and technically sophisticated, with the result that they are also vulnerable.

5 As a rule the problem is how to expel the exhaled air while avoiding having an excessively large opening out of the mouthpiece/nosepiece which also acts as an entry point for moisture, etc. In addition it is important to carry exhaled air away from the area immediately round the nose and mouth since the inhalation air is drawn from this nearby area and there is a risk of exhaled CO₂-rich air being
10 breathed back in.

It is therefore an object of the present invention to provide a system for use in helmets or face masks covering the nose/mouth, which system permits the free passage of exhaled gases away from the face only by means of the natural velocity of the gases out of the nose or mouth. It is a further object to provide a system
15 which can easily be adapted to the different helmets and face masks and which does not come into conflict with padding, the ability to tilt up a chin guard or the like.

Thus, based on the above-mentioned objects, an exhalation system is provided for a helmet or face mask, which helmet or face mask covers the whole or parts of the area of the face's exhalation organs, the nose and mouth, with a chin guard. The
20 system is characterised in that the chin guard is provided with an internal closed cavity which has an opening towards the interior of the helmet or the face mask on the inside of the chin guard and an additional opening towards the outside of the chin guard. The opening towards the interior of the helmet is relatively large and is in the form of one large opening or a small number of large openings which offer
25 the least possible resistance and which maintain the velocity of the exhalation air in the best possible manner.

In an alternative embodiment the chin guard is composed of two parallel plates with an intermediate cavity where the cavity is airtight at the upper edge, thus preventing exhaled air from moving up from the cavity (it is a well-known fact that hot air
30 rises).

In a further embodiment the cavity in the chin guard has an opening in the lower edge of the chin guard for venting exhaled air. This provides amongst other advantages a short ventilation path.

In yet another embodiment the venting of exhaled air can be implemented, for
35 example, on the side of the chin guard through one or more openings. This embodiment has the added advantage that a slight negative pressure can be created on the sides which helps to "suck" out exhaled air when, for example, the air is moving past the exterior of the helmet at high speed.

In an alternative embodiment a respirator may be connected to the helmet, with the result that inhaled air is first purified or an excess pressure of "clean" air is established inside the helmet. In connection with the exhalation system, a respirator of this kind can be connected to the cavity in the chin guard. However, such a
5 solution requires a good seal round the neck and back of the head as well as in the remaining parts of the helmet.

An example of a helmet with chin guard and exhalation system according to the present invention is further illustrated in figure 1. A helmet 1 is illustrated here in perspective from behind and partly below with a chin guard 2. The chin guard 2 also
10 has a raised portion 6 at the exhalation organs, which is preferred in order to capture as much of the exhaled air as possible.

The chin guard 2 is further provided with a cavity 3 at the front edge with a large opening 4 from the inside of the helmet towards the cavity 3. The cavity 3 is airtight along its outer edge except for an opening 5 at the bottom where the exhaled air can
15 be expelled freely.

The inhalation takes place in the immediate vicinity of the nose and mouth and will therefore not be affected to a noticeable extent by the exhaled air that has passed to the outside of the bottom of the helmet. If there is a relative difference in velocity between the helmet and the surrounding air, moreover, exhaled air which is passed
20 down on the bottom of the chin guard will blow away or be attenuated.

The opening 4 into the cavity 3 is adapted in size and shape in order to maintain the natural velocity of the exhaled air and this air is then diverted from the immediate , vicinity of the breathing organs.

PATENT CLAIMS

1. An exhalation system for a helmet or face mask, which helmet or face mask covers the whole or parts of the area of the face's exhalation organs, the nose and mouth, with a chin guard,
5 characterised in that the chin guard is provided with an internal closed cavity which has at least one opening towards the interior of the helmet or the face mask on the inside of the chin guard and that the cavity is further provided with one or more openings towards the outside of the chin guard.
2. An exhalation system according to claim 1,
10 characterised in that chin guard consists of two parallel plates with an intermediate cavity and that the cavity is airtight at the upper edge.
3. An exhalation system according to claims 1-2,
characterised in that the cavity in the chin guard has an opening in the lower edge of the chin guard.
- 15 4. An exhalation system according to claims 1-3,
characterised in that the cavity has one or more openings towards the outside of the chin guard, on the side of the chin guard.

INTERNATIONAL SEARCH REPORT

International application No.

PCT/NO 2003/000358

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: A43B 3/24 // A43B 3/28, A62B 18/08

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: A43B, A62B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, WPI DATA, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5758639 A (IKONEN), 2 June 1998 (02.06.1998) --	
A	US 4612675 A (BROERSMA), 23 Sept 1986 (23.09.1986) -- -----	

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

16 January 2004

Date of mailing of the international search report

03 -02- 2004

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Sune Söderling / JA A
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

Information on patent family members

24/12/2003

International application No.

PCT/NO 2003/000358

US	5758639	A	02/06/1998	DE	69318167	D,T	22/10/1998
				EP	0661937	A,B	12/07/1995
				FI	89872	B,C	31/08/1993
				FI	924020	D	00/00/0000
				FI	924345	D	00/00/0000
				JP	8504235	T	07/05/1996
				WO	9405175	A	17/03/1994

US	4612675	A	23/09/1986	NONE
----	---------	---	------------	------

